

BIOCLEANER 7500 DIELECTRIC DEGREASING SOLVENT

Línea Especialidades Químicas

Catálogo de productos CONTYQUIM® | 2023



CHARACTERISTICS

The heavy duty evaporative moderate degreaser that removes contaminant seconds.

- Cleaner - Extra-strong degreaser with a mild odor and rapid evaporation.
- Removes contaminants in seconds without leaving residues.
- Does not contain CFCs, trichloroethane, or substances that deplete the ozone layer.
- Does not contain carcinogenic substances.
- Dries faster than terpene-based solvents.
- Safe on most surfaces.
- No need for rinsing.
- Controlled evaporation.
- Non-conductive.

OVERVIEW

NAME	CAS	SYNONYM	FORMULA	PRESENTATION
BIOCLEANER 7500	ND	ND	ND	TM200 L

SPECIFICATIONS AND ANALYSIS METHOD

Analysis Type	Specifications	Method
Spontaneous Ignition Temperature	>442°F (228°C)	Internal
Boiling Point	320°F – 392°F (160 °C– 200°C)	Internal
Density g/mL	0.750 – 0.850	Internal
Viscosity @ 25°C	200 cP – 800 cP	Internal
Color	Colorless	Internal
Odor	Characteristic	Internal
Temperature Range° F (° C)	-40°F – 175°F (-40°C – 79°C)	Internal
Vapor Pressure	2.6 mmHg @ 20°C	Internal
Pour Point	0°F (-18°C)	Internal

Stowage and Storage

MATERIAL	Polietileno
PESO TOTAL (LBS.)	77
CAP. DE CARGA (LBS.)	6,1000
CAP. DE DERRAME	7.3 Gal.
DIMENSIONES LARGO x ANCHO x ALTO	49 x 49 x 11"

RECOMMENDED USE OF SPILL PALLET

Maximum Stacking: 2 layers
 Calculation / Containers: 50 liters (max.)
 Stack on Pallet: Plastic or Wood

Contactanos: >

www.contyquim.com

Teléfono

(442) 209 5050 al 52

Correo

e-ventas@contyquim.com

APPLICATIONS

Efficient in degreasing and cleaning electric motors, starters, switches, rotors, capacitors, coils, pumps, distributors, etc. Safe to use, with fast action.

METHOD

Can be applied by immersion, spraying, brushing, or rubbing. Apply directly to the surface to be cleaned, let it act for a few minutes, and dry with compressed air, cloth, or rag. For safety reasons, it is not recommended to apply directly to motors or electric machines in operation. Always check the shutdown switch.

INSTRUCTIONS FOR USE

- Apply in well-ventilated areas. If necessary, use a fan to prevent vapor buildup.
- Keep the container 15 to 25 cm away from the area to be cleaned.
- Use the extension tube for hard-to-reach areas.
- Drying is not necessary.

HANDLING AND SAFETY

It is recommended that the product handler/operator use personal protective equipment, including safety goggles and nitrile gloves.

HANDLING, TRANSPORT, AND STORAGE CONDITIONS

Protect from sunlight. Store in a well-ventilated place. Keep away from heat, sparks, open flames, hot surfaces, and other sources of ignition. No smoking. Do not spray on an open flame or any other ignition source. Do not pierce or burn, even after use.

OBSERVATIONS

The information provided in this document is a faithful copy of the technical data sheet from the manufacturer or distributor, compiled under CONTYQUIM criteria. It contains useful technical information about the product. It is the responsibility of the user to follow and be aware of the information to achieve the best quality and durability of the product.